IMPORTANT! Please Read

Conventional serological pipetting

When
you first receive
your ali-Q™ 2,
press the purple
button to wake it
out of shipping
mode.



Note:

- 1. The motor will activate at seemingly random times when pressing the aspirate or dispense buttons. Don't worry. It's normal!
- 2. ali-Q 2 will go into sleep mode after 3 minutes of non-use but will wake with any movement of the unit.

For more information on ali-Q's intelligent measuring system, see Operating Manual at www.vistalab.com/support

Aliquoting/repeat pipetting



ali-Q 2 VS model only:

Set desired aliquoting speed using speed dial



aliquot button



All ali-O 2 models:

- 1. Set aliquot volume on aliquot dial.
- Aspirate adequate volume for total number of desired aliquots.
- Press and HOLD the purple aliquot button until the aliquot is dispensed. You will hear and feel the motor come on. Repeat press and hold for each aliquot. For maximum precision, discard first aliquot.

Note: if you don't hold the button long enough for the full aliquot volume, you will hear an "alert" sound and red light will flash.



Description	Catalog #
ali-Q 2 pipet controller	2100-0005
ali-Q 2 LS pipet controller	2100-0003
ali-Q 2 VS 5mL pipet controller	2100-1005
ali-Q 2 VS 10mL pipet controller	2100-1010
Additional box contents:	
spare 0.22µm membrane filter	9020-4003
power supply w/outlet adapters	9020-9005
wall mount	9020-9008
calibration certificate	

Register your ali-Q 2 online at www.vistalab.com

for 1 year Warranty

Go to www.vistalab.com/support for full Operating Manual



Complete your optimal liquid handling system with Wobble-not™ serological pipets Catalog

Standard Length 5 mL (200/cs) 4090-0005 10 mL (200/cs) 4090-0010 25 ml (200/cs) 4090-0025 50 mL (100/cs) 4090-0050 100 mL (50/cs) 4090-0100 **Shorty Length** 10 mL (200/cs) 5090-0010



